C1 Cntd Sub D1

an array of non-contact electrodes on said distal end of said body, said array having a proximal end and a distal end, wherein said non-contact electrodes are linearly arranged along a longitudinal axis of said body; and

at least one location sensor on said distal end of said body for generating signals used to determine a location of said contact electrode and a location of said non-contact electrodes, the location of the non-contact electrodes determined by said signals generated by said at least one location sensor, said location of the non-contact electrodes defining a cloud of space representing a minimum volume of the chamber geometry of the heart.

This is claimed not a positive limitation

by what

No signals have been generated its only functionally claimed

C2 Sub D1

Claim 12. (Three Times Amended) A catheter for mapping a chamber of the heart comprising:

a body having a proximal end and a distal end, said distal end having a distal tip;

an array of non-contact electrodes on said distal end of said body, said array having a proximal end and a distal end, wherein said non-contact electrodes are linearly arranged along a longitudinal axis of said body; and

at least one location sensor proximate to said distal tip for generating signals used to determine a location of said non-contact electrodes, the location of said non-contact electrodes determined by said signals generated by said at least one location sensor, said location of the non-contact electrodes defining a cloud of space representing a minimum volume of the chamber geometry of the heart.

same as above

C3 Sub D1

Claim 16. (Three Times Amended) A method for generating an electrical map of a chamber of a heart, said map depicting an electrical characteristic of the chamber as a function of chamber geometry, said method comprising the steps of:

a) providing a catheter comprising a body having a proximal end and a distal end, said distal end having a distal tip; a contact electrode at said distal tip; an array of non-contact electrodes on said distal end of said body, said array having a proximal end and a distal end, wherein said non-contact electrodes are linearly arranged along a longitudinal axis of said body; and at least one location sensor on said distal end of said body;

b) advancing said catheter into said chamber of said heart;

c) determining a location of said contact electrode and a location of said non-contact electrodes using said at least one location sensor wherein the location of said non-contact electrodes defines a cloud of space;

d) contacting a wall of said chamber of said heart with said contact electrode at a plurality of contact points;

e) acquiring electrical information and location information from each of said electrodes and said at least one location sensor, respectively, said acquisition taking place over at least one cardiac cycle while said contact electrode is in contact with each of said contact points; and

f) determining a minimum volume of said heart chamber geometry using the location of said non-contact electrodes;

g) generating an electrical map of said heart chamber from said acquired location and electrical information.

Claim 35. (Three Times Amended) A method for generating an electrical map of a chamber of a heart, said map depicting an electrical characteristic of the chamber as a function of chamber geometry, said method comprising the steps of:

a) providing a catheter comprising a body having a proximal end and a distal end, said distal end having a distal tip; an array of non-contact electrodes on said distal end of said body, said array having a proximal end and a distal end, wherein said non-contact electrodes are linearly arranged along a longitudinal axis of said body; and at least one location sensor proximate to said catheter distal tip;

b) advancing said catheter into said chamber of said heart;

c) determining a location of said non-contact electrodes using said at least one location sensor wherein the location of said non-contact electrodes defines a cloud of space;

d) contacting a wall of said chamber of said heart with said catheter distal tip at a plurality of contact points;

e) acquiring electrical information and location information from each of said non-contact electrodes and said at least one location sensor, respectively, said

acquisition taking place over at least one cardiac cycle while said catheter distal tip is in contact with each of said contact points;

f) determining a minimum volume of said heart chamber geometry using the location of the non-contact electrodes; and

g) generating an electrical map of said heart chamber from said acquired location and electrical information.

Claim 42. (Three Times Amended) Apparatus for generating an electrical map of a chamber of a heart, said map depicting an electrical characteristic of the chamber as a function of chamber geometry, said apparatus comprising:

a catheter including a body having a proximal end and a distal end, said distal end having a distal tip; a contact electrode at said distal tip; an array of non-contact electrodes on said distal end of said body, said array having a proximal end and a distal end, wherein said non-contact electrodes are linearly arranged along a longitudinal axis of said body; and at least one location sensor on said distal end of said body for generating signals used to determine a location of said contact electrode and a location of said non-contact electrodes, the location of the non-contact electrodes determined by said signals generated by said at least one location sensor, said location of the non-contact electrodes defining a cloud of space representing a minimum volume of the chamber geometry of the heart; said catheter being adapted to contacting a wall of said chamber of said heart with said contact electrode at a plurality of contact points; and a signal processor operatively connected to said catheter for acquiring electrical information and location information from each of said contact electrode and said non-contact electrodes and location sensors, respectively, over at least one cardiac cycle while said contact electrode is in contact with each of said contact points, said signal processor also generating an electrical map of said heart chamber from said acquired location and electrical information.

Claim 47. (Three Times Amended) Apparatus for generating an electrical map of a chamber of a heart, said map depicting an electrical characteristic of the chamber as a function of chamber geometry, said apparatus comprising:

a catheter including a body having a proximal end and a distal end, said distal end having a distal tip; an array of non-contact electrodes on said distal end of said body, said array having a proximal end and a distal end, wherein said non-contact electrodes are linearly arranged along a longitudinal axis of said body; and at least one location sensor proximate to said catheter distal tip for generating signals used to determine a location of said non-contact electrodes, the location of said non-contact electrodes determined by said signals generated by said at least one location sensor, said location of said non-contact electrodes defining a cloud of space representing a minimum volume of the chamber geometry of the heart; said catheter being adapted to contacting a wall of said chamber of said heart with said catheter distal tip at a plurality of contact points; and a signal processor for acquiring electrical information and location information from each of said electrodes and location sensors, respectively, over at least one cardiac cycle while said catheter distal tip is in contact with each of said contact points; said signal processor also generating an electrical map of said heart chamber from said acquired location and electrical information.